



A&T[™]



AirCast AC

Elevating presentation experiences - wirelessly

BYOD

Wireless Collaboration Device

AirCast AC

SPECIFICATION



Technical Specifications	Receiver AC
System	Linux
RAM	256 MB
ROM	512 MB
Interface	HDMI OUT 1.4*1, USB*3, RJ45*1, Audio*1, DC Power Jack*1
Video Outputs	HDMI 1.4, comply with HDCP
Frame Rate	Up to 30 fps depending on environment (UHD)
Output Resolution	Max 3840*2160P(4K)
Input Resolution	Max 3840*2160P(4K)
Simultaneous Connections	32
Max. Display Windows	4
No.of Dongle Supported	8
Native Protocol	Miracast, Airplay
Wireless Transmission Band	2.4 GHz & 5 GHz (Dual band Wi-Fi)
USB Touchback Support	Yes
Wireless Transmission Protocol	IEEE 802.11 a/g/n/ac
Authentication Protocol	WPA2-PSK(Pre-Share Key)
Wireless Speed	TX 300Mbps
Receiving Distance	No obstacle 50m
Support OS	Windows7/8/10, Mac OS, Chrome OS, Android, Linux, IOS 8.0 and above
Power Supply	DC5V, 2A
Power Consumption	12W
Dimension(W*H*D)	120mm X 120mm X 20mm
Operating Temperature	0°~ 40°C



+91 452 4392222

sales@atnetindia.net

www.atnetindia.net

CONNECTING YOU **ACROSS SPACE AND TIME**