


# AVX 3.2

USB & HDMI  
Camera Switcher & Mixer

**Applications** : Meeting Room, Lecture Room, Web - cast




**CAMERA SWITCHER**



**CAMERA MIXER**



**FLEXIBLE LAYOUT**



**PLUG & PLAY**



# AVX 3.2

## SPECIFICATION

### Parameters

Video Input	1x USB 3.0, 1x USB 2.0, 1x HDMI 1.4
Video Input Resolution	HDMI : 1920x1080@60Hz, 1280x720@60Hz USB3.0: 1920x1080@30Hz, 1280x720@30Hz etc. USB2.0: 1920x1080@30Hz, 1280x720@30Hz etc.
Video Output	1x USB3.0 Type-C, 1x HDMI
Video Output Resolution	HDMI : 3840x2160@60Hz, 3840x2160@30Hz, 1920x1080@60Hz, 1280x720@60Hz Type C : 1920x1080@30Hz, 1280x720@30Hz etc.
Format Compliance	HDMI1.4, HDCP1.4
Audio	1x analog out, line level 3.5mm jack 1x analog in, line level 3.5mm jack
Control options	Integrated Buttons, LAN, USB HID, RS-232
IP interface	1x 1000Mbps, POE option (802.3af)
Dimension	180mm x 95mm x 18mm
Operating Temperature	0° C to +45° C
Storage Temperature	0° C to +60° C
Relative humidity	20%~ 85% RH (no condensation)
DC Power	12V
Power Consumption	15W(MAX)
Power adapter	AC100~240v 50/60Hz 12V/1.5A

