



**A&T**<sup>™</sup>



# **PTC20N V.5**

PTZ CAMERA


**Applications:** Board Room | Class room | Seminar Hall | Lecture Hall



1080P  
FULL HD



20X  
OPTICAL ZOOM



USB + HDMI + SDI + RJ45



BUILT IN STREAMING  
SUPPORT



A&T

# PTC20N V.5

## SPECIFICATION



Camera	
Image Sensor	1/2.8" CMOS, 2.14 MP
Iris	F1.6 ~ F3.5
Focal Length	4.7mm ~ 94mm
HFOV	60°~ 2.9°
Optical zoom	20x
Other Camera Data	
Digital Zoom	16x
Focusing System	Auto, Manual, PTZ Trigger, One Push Trigger
Shutter Speed	1/50 ~ 1/10,000s
AGC	Auto, Manual
BLC	Support
White Balance	Auto, One Push, Manual, ATW, Static Color Temperature
Wide Dynamic Exposure	Support
SNR	Auto, Manual, Shutter Priority, Iris Priority, Brightness Priority
	≥50dB
Interface	
HDMI	1080P60/P50/P30/P25, 720P60/P50/P30/P25, 480P60/P50/30/25
Network	1×RJ45:1×10M/100M(Support POE) 1. Video Output Format: Max 1080P60; 2. Image Compression: H.264/H.265 3. Protocol: ONVIF/RTSP/RTMP/TCP/UDP/SRT; 4. Audio Compression: AAC 5. Support multiple stream
USB 3.0	1. Support UVC1.1 2. UVC Support: H.264/H.265/MJPEG: 1080P60/P50/P30/P25, 720P60/P50/P30/P25, 480P60/P50/P30/P25, 360P60/P50/P30/P25 YUY2:1080P30/P25, 720P30/P25, 480P30/P25, 360P30/P25 3. UAC Audio Format PCM
3G-SDI	1080P60/P50/P30/P25, 720P60/P50/P30/P25
Audio	1×LINE IN, 3.5mm
Control Interface	1×RS-232 In, 1×RS-232 Out/RS-485
TF Card	Max support 256G
PTZ	
Pan	-170° ~ +170°; 0.1° ~ 120°/s
Tilt	-30° ~ +90°; 0.1° ~ 90°/s
Preset Number	256
General	
Power	DC12V; <15W
Control Protocol	VISCA (support daisy chain) / PELCO-P / PELCO-D
Operating Temperature	0°C ~ +40°C
Storage Temperature	-20°C ~ +60°C
Dimensions (L×W×H)	176mm × 137mm × 171mm
Weight	≤1.2kg

+91 452 4392222

sales@atnetindia.net

www.atnetindia.net