



**A&T**<sup>™</sup>



# **KLICK U2**

USB PTZ CAMERA

## Applications: Conference Room | Board Room | Classroom



1080P  
FHD / 4K



72.5° (12X)  
69° (10X)  
81° (3X)




12X / 10X / 3X  
OPTICAL ZOOM



16X/5X  
DIGITAL ZOOM



USB 3.0, HDMI,  
RJ45 INTERFACES



# KLICK U2

## SPECIFICATION



MODEL	Klick U2-12X	Klick U2-10X	Klick U2-3X
<b>Camera</b>			
Image Sensor	1/2.8" CMOS, 2.14MP	1/2.8" CMOS, 2.14MP	1/2.8" CMOS, 8 MP
IRIS	4.14mm ~ 47.08mm	4.3mm ~ 43mm	3.3mm ~ 9.7mm
Aperture value	F1.2 ~ F2.8	F1.6 ~ F3.0	F2 ~ F3.7
HFOV	72.5° ~ 6.3°	71° ~ 8°	81° ~ 31.3°
Optical zoom	12X	10X	3X
Digital Zoom	16X	16X	5X
Focusing System	Auto/Manual		
Shutter speed	1/50 ~ 1/10,000s		
Gain	Auto, Manual		
White Balance	Automatic, Manual, Automatic tracking, One Push, Static Color Temperature		
BLC	Support		
Wide Dynamic	Support		
Exposure	Auto, Manual, Shutter Priority, Iris Priority, Brightness Priority		
SNR	≥50dB		
<b>PTZ</b>			
Pan	-170° ~ +170°; 0.1° ~ 100°/s		
Tilt	-30° ~ +90°; 0.1° ~ 70°/s		
Preset Number	256		
<b>Interface</b>			
HDMI	1080P60/P50/P30/P25, 720P60/P50		NA
Network	1×RJ-45:1×10M/100M Video Output Format:Max 1080P60; 2. Image Compression:H.264/H.265 1080P60/P50/P30/P25, 720P60/P50/P30/P25, 360P60/P50/P30/P25; Protocol:ONVIF/RTSP/RTMP/TCP/UDP/RTMPS/GB28181; Audio Compression: AAC & Support dual streams		
USB 3.0	Support UVC1.1 & UVC Support: H.264/H.265/MJPEG, Video resolution:1080P60/P50/P30/P25, 720P60/P50/P30/P25, 480P60/P50/P30/P25, 360P60/P50/P30/P25 YUY2:1080P30/P25, 720P30/P25, 480P30/P25, 360P30/P25 UAC Audio Format PCM		
Audio	1×LINE IN, 3.5mm		
Control Interface	1×RS-232 In, 1×RS-232 Out/RS-485		NA
<b>General</b>			
Power	DC12V; <8W		
Control Protocol	VISCA (support daisy chain) / PELCO-P / PELCO-D		NA
Operating Environment	Temperature: 0°C ~ +40°C, Relative Humidity: 10%RH ~ 90%RH		
Storage Environment	Temperature: -20°C ~ +60°C, Relative Humidity: 10%RH ~ 95%RH		
Dimensions (LxWxH)	176mm × 137mm × 171mm		
Weight	≤1.2kg		

+91 452 4392222

sales@atnetindia.net

www.atnetindia.net